



Certificate number: 2509739 (3)

Issued 04/12/2025

Expires 29/09/2030

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Geberit Sales Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

#### Certificate Issued to:

Geberit Sales Ltd  
Geberit House  
Edgehill Drive  
Warwick  
CV34 6NH  
United Kingdom



KUKreg4

# Product Certificate

Appendix to Certificate number: 2509739

The following products belong to this certificate

<p><b>PRODUCT DESCRIPTION</b>  Range of side entry inlet vales to BS1212 PART 4 2016 incorporating plastic bodies.  ATS3 – Without Production Surveillance.</p>
<p><b>MODEL(S)</b>  Type 383 filling valve  244.510.00.5 (with long thread)  244.595.00.5 (with splash guard)  245.894.00.5 (with long thread)  851.044.00.0 (with short thread)</p>
<p><b>SIZE:</b>  3/8" BSP or 10mm compression</p>
<p><b>SCOPE:</b>  Manufacturer recommended maximum working pressure 10.0 Bar &amp; maximum operating temperature cold water use only.  Hygienic Purposes: Non-metallic materials suitable for continuous use for cold water use only.</p>
<p><b>MARKING</b>  Geberit on body.  Model, BS1212-4 &amp; EN14124/1 on adhesive label on body.</p>
<p><b>MATERIALS</b>  Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p><b>BACKFLOW PROTECTION NOTES</b>  N/A.</p>
<p><b>ADDITIONAL NOTES</b>  All water contact &amp; exposed components satisfy opacity requirements.  Suitable for use in a WC suite, provided it forms an arrangement which meets the requirements of Type AUK1 and an appropriate WC performance specification. Please refer to the clarification of the requirements of the Water Supply (Water Fittings) Regulations, Byelaws in Scotland, as they apply to Type AUK1 air gaps in WC suites.</p>

**Extra Notes**